

Bitsadmin getdisplayname and bitsadmin geterror command in Windows

The bitsadmin getdisplayname command takes the display name of the specified task. The bitsadmin geterror command retrieves detailed error information for the specified job.

The bitsadmin getdisplayname command takes the display name of the specified task. The bitsadmin geterror command retrieves detailed error information for the specified job.

Bitsadmin getdisplayname and bitsadmin geterror command in Windows

1. Bitsadmin command getdisplayname
 1. Syntax
 2. Parameters
 3. For example
2. Bitsadmin geterror command
 1. Syntax
 2. Parameters
 3. For example

Bitsadmin command getdisplayname

Syntax

```
bitsadmin / GetDisplayName
```

Parameters

ParameterDescriptionJob Display name of the task or GUID.

For example

The following example retrieves the display name for the task named **myDownloadJob**.

```
C:> bitsadmin / GetDisplayName myDownloadJob
```

Bitsadmin geterror command

Syntax

```
bitsadmin / GetError
```

Parameters

ParameterDescriptionJob Display name of the task or GUID.

For example

The following example retrieves the error information for the task named **myDownloadJob**.

```
C:> bitsadmin / GetError myDownloadJob
```

See more:

1. The command bitadmin addfilewithranges in Windows
2. Bitsadmin create command in Windows
3. Bitsadmin complete command in Windows

You finished reading the article "**Bitsadmin getdisplayname and bitsadmin geterror command in Windows**" edited by the [TipsMake](#) team. We hope this article has provided you with many useful tech tips and tricks. You can search for similar articles on tips and guides. Thank you for reading and for following us regularly.