

Class properties in HTML

In HTML, class properties are used to identify one or more class names for HTML elements.

In HTML, class properties are used to identify one or more class names for HTML elements. Class names can be used in CSS or JavaScript to perform certain tasks for elements named that class. In CSS, to select an element with a special class, add a dot (.) And then enter the class name.

Examples use CSS to style all elements with the class name 'city'

Hanoi

Hanoi is the capital of Vietnam.

Paris

Paris is the capital of France.

Tokyo

Tokyo is the capital of Japan.

The results displayed will look like the following.



The class attribute applies to many elements

Note:

1. `class` properties can be used with any HTML element.
2. The class name distinguishes between uppercase and lowercase letters.

Use class properties in JavaScript

JavaScript can access certain class-named elements with `getElementsByClassName()`

For example, when a user clicks a button, hiding all elements with the class name is 'city'.

Use multiple layers in HTML

HTML elements can use multiple class names, each with a space separated by a space. For example, you can style elements with the 'city' and 'big' layers.

London

Paris

Tokyo

Same class but different cards

Different cards like

good

can use the same class name (and have the same style).

Hanoi

Hanoi is the capital of Vietnam.

Previous lesson: Block and inline elements in HTML

The following article: id attribute in HTML

You finished reading the article "**Class properties in HTML**" edited by the [TipsMake](#) team. We hope this article has provided you with many useful tech tips and tricks. You can search for similar articles on tips and guides. Thank you for reading and for following us regularly.