

Clone activity in Git

We have an empty repository on the server and Tom also pushed his first version. Now, Jerry can observe his changes. Clone operation creates a remote repository instance.

We have an empty repository on the server and Tom also pushed his first version. Now, Jerry can observe his changes. Clone operation creates a remote repository instance.

Jerry creates a new folder in his home directory and performs the simulation.

```
[jerry @ CentOS ~] $ mkdir jerry_repo  
[jerry @ CentOS ~] $ cd jerry_repo /  
[jerry @ CentOS jerry_repo] $ git clone gituser@git.server.com: project.git
```

The above command will produce the following result:

```
Initialized empty Git repository in /home/jerry/jerry_repo/project/.git/  
remote: Counting objects: 3, done.  
Receiving objects: 100% (3/3), 241 bytes, done.  
remote: Total 3 (delta 0), reused 0 (delta 0)
```

Jerry changed this directory to the new local directory and listed its directory contents.

```
[jerry @ CentOS jerry_repo] $ cd project /  
[jerry @ CentOS jerry_repo] $ ls  
README
```

According to Tutorialspoint

Previous lesson: Create activity in Git

Next article: Make changes in Git

You finished reading the article "**Clone activity in Git**" edited by the [TipsMake](#) team. We hope this article has provided you with many useful tech tips and tricks. You can search for similar articles on tips and guides. Thank you for reading and for following us regularly.