

Secedit: validate command in Windows

Secedit: validate command to authenticate security settings stored in security templates (.inf files).

Secedit: validate command to authenticate security settings stored in security templates (.inf files). To better understand how to use this command, see the example below.

Secedit: validate command syntax

```
Secedit / validate
```

Secedit: validate command parameter

Parameters

Describe

Tên t?p tin c?u hình

This is a required parameter.

Specify the path and file name for the security template to be authenticated.

Secedit command: validate

1. Validating security patterns will be useful if a template is corrupted or installed incorrectly.
2. An invalid security form will not be applicable.
3. The log file will not be updated.
4. Starting with Windows Server 2008, the Secedit / refreshpolicy subcommand has been replaced with gpupdate. For more information on how to refresh security settings, see the Gpupdate command.

Secedit: validate command example

After the rollback process is performed on a security template, you want to verify that the inf rollback, secRBKcontoso.inf file, is valid, enter:

```
Secedit / validate secRBKcontoso.inf
```

See more:

1. Summary of 20 common Run commands on Windows operating system
2. Instructions for installing Windows Server 2012 step by step
3. Install Windows Server 2008

You finished reading the article "**Secedit: validate command in Windows**" edited by the [TipsMake](#) team. We hope this article has provided you with many useful tech tips and tricks. You can search for similar articles on tips and guides. Thank you for reading and for following us regularly.
