

# Test on JAVA P10 test

Multiple choice questions on Java programming help you test your basic knowledge of this programming language. The set of questions includes 10 sentences to try.

1. Question 1. Given str = 'Yunlin university', what is the result of str.lastIndexOf('i')?
  1. 4
  2. 14
  3. 7
  4. There is no right answer
2. Question 2. Given str = 'Yunlin university', what is the result of str.lastIndexOf('i', 7) returning results?
  1. 4
  2. 14
  3. 7
  4. -first
3. Question 3. Given str = 'Yunlin university', what is the result of str.lastIndexOf('sti')?
  1. 4
  2. 14
  3. false
  4. -first
4. Question 4. After running the command block s =?

```
int s = 0;

for (int i = 3; i <= 10; i++)

s += i;
```

1. 42
2. 55
3. 9
4. 29

5. Question 5. After running the command block s =?

```
for (int i = 0; i <= 10; i++) {

int s = 0;

s += i;}

System.out.print (s);
```

1. 0
2. 55

3. 45

4. Wrong command

6. Question 6. After running the command block s =?

```
int s = 0;

for (int i = 0; i = 10; i ++)
```

s + = i;

1. 45

2. 55

3. 56

4. 0

7. Question 7. If the program runs with the java message -g cruel world command, what is the value of the args [1] parameter?

```
public static void main (String [] args) {

if (args [0] .equals ('- g'))

System.out.print ('Goodbye,');

for (int i = 1; i

System.out.print ('' + args [i]); }
```

1. -g

2. cruel

3. world

4. -g cruel world

8. Question 8. If the program runs with the java message -g cruel world, what is the result?

```
public static void main (String [] args) {

if (args [0] .equals ('- g'))

System.out.print ('Goodbye,');

for (int i = 1; i

System.out.print ('' + args [i]); }
```

1. -g cruel world

2. cruel world

3. Goodbye, cruel world

4. Goodbye cruel world

9. Question 9. If initializing two class A objects extending KiemTra and class B extends KiemTra, the id of object A is valid:

```
class KiemTra {
```

```
private int i;

private int nextId;

public void setId () {

    id = nextId;

    nextId ++;

}

}
```

1. 0
2. first
3. 2
4. Void

10. Question 10. If initializing two class A objects, the KiemTra and class B extends extends KiemTra, the id of object B is valid?

```
class KiemTra {

    private int i;

    private int nextId;

    public void setId () {

        id = nextId;

        nextId ++;

    }

}
```

1. 0
2. first
3. 3
4. Void

You finished reading the article "**Test on JAVA P10 test**" edited by the [TipsMake](#) team. We hope this article has provided you with many useful tech tips and tricks. You can search for similar articles on tips and guides. Thank you for reading and for following us regularly.